

Material Safety Data Sheet

Issued: 04/26/2010

Revision Number: 2

1. Identification of Substance /Preparation and Company /Undertaking

Product Name: CHOICE 2 Light-Cure Veneer Cement
Manufacturer: Bisco, Inc. 1100 W Irving Park Road, Schaumburg, IL 60193 USA
Telephone: 1-847-534-6000, during normal business hours

Emergency CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Telephone Number: Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

EC Representative: Bisico France, 120, allée de la Coudoulette, 13680 Lançon de Provence, France
Telephone: 33-4-90-42-92-92

2. Composition/Information on Ingredients

| Ingredient | Concentration Range (%) | CAS Number | Symbol/Risk Classificaton | OSHA PEL (mg/m3) | ACGIH (mg/m3) | LD50 (mg/kg, rat/oral) |
|-------------------|-------------------------|--------------|---------------------------|------------------|---------------|------------------------|
| Strontium Glass. | <75. | 65997-18-4. | N/A. | 15. | 10. | N/D. |
| Amorphous Silica. | <25. | 112945-52-5. | N/A. | 15. | 10. | >10000. |
| Bis-GMA | <10 | 1565-94-2 | Xi; R36/38-43 | N/D | N/D | N/D |

3. Hazards Identification

Irritates the eye and skin. May cause allergic reaction on skin.

4. First-aid Measures

Inhalation: Provide fresh air and rest.
Skin Contact: Wash with soap and water.
Eye Contact: Flush with running water for at least 15 minutes while keeping eye lids open; seek medical attention.
Ingestion: Drink two glasses of water or milk. Seek medical attention if a substantial amount has been ingested.

5. Fire-fighting Measures

Fire-fighting media: Dry chemical powder, foam or carbon dioxide.
Fire and explosion risks: Upon combustion, irritating gases may form.

6. Accidental Release Measures

Personal Precautions: Prevent skin/eye contact.
Environmental Precautions: Avoid ground water contamination.
Methods for Cleaning Up: Wipe with damp paper towels. Discard properly.

7. Handling and Storage

Avoid high light intensity >10000 lux, Store in ventilated cool dry place (<22C/ 72F).

8. Exposure Controls /Personal Protection

Eye Protection: Use protective eyewear.

Hand Protection: Use protective gloves.

Respiratory Protection: Avoid prolonged breathing of vapors of uncured material.

Skin Protection: Use Any necessary hygiene measures.

9. Physical / Chemical Properties

| | | | |
|-----------------------|---------------------|--------------------------|-----|
| Appearance | Viscous resin paste | Vapor Pressure @ 20C/68F | N/A |
| Color | Tooth colored | Miscibility | N/A |
| Odor | Slight acrylic odor | Vapor Density | N/A |
| Solubility (H2O, fat) | Insoluble | pH | N/A |
| Boiling Point / Range | N/A | Evaporation Rate | N/A |
| Melting Point / Range | N/A | Viscosity | N/A |
| Flash Point | >75 C / 167F | Partition Coefficient | N/A |
| Conductivity | N/A | Autoflammability | N/A |
| Explosive Properties | N/A | Flammability | N/A |
| Oxidizing Properties | N/A | Relative Density | N/A |

10. Stability and Reactivity

Avoid high temperatures.

11. Toxicological Information

Eye Contact: Irritates the eyes.

Skin Contact: May irritate the skin.

Sensitization: May cause allergic reaction on contact with the skin.

Other: N/A.

12. Ecological Information

N/A

13. Disposal Considerations

Refer to any Community provisions relating to waste. In their absence, refer to National or Regional provisions relating to waste.

14. Transport Information

No special precautions.

15. Regulatory Information

Classification: Xi; Irritant. R36 Irritating to eyes. R38 Irritating to skin. R43 May cause sensitization by skin contact.

Safety: Refer to any applicable National laws.

16. Other Information

Revision Date: 04/26/2010 Replaces MSDS dated: 06/20/2006

Revision Number: 2 Product: CHOICE 2 Light-Cure Veneer Cement

This information is believed to be correct as of the date of this MSDS. The manufacturer makes no representation as to the completeness or accuracy of this information and supplies it on the condition that the person receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

NOTE: CHEMTREC provides an emergency telephone number in the event of an emergency for leak, fire, exposure or accident involving the hazardous material that is being shipped. All non-emergency inquiries should be directed to Bisco during normal working hours.