

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 6/26/2023 Supersedes: 1/19/2018 Version: 2.0

1.1. Identification Product form : Mixture Product name : Aelite Aesthetic Enamel 1.2. Recommended use and restrictions on use Use of the substance/mixture : For Rx Only 1.3. Supplier Manufacturer BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL , 60193 U.S.A.			
Product name : Aelite Aesthetic Enamel 1.2. Recommended use and restrictions on use Use of the substance/mixture : For Rx Only 1.3. Supplier Manufacturer BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL, 60193			
Use of the substance/mixture : For Rx Only 1.3. Supplier Manufacturer BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL, 60193			
1.3. Supplier Manufacturer BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL , 60193			
Manufacturer BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL , 60193			
BISCO, Inc. 1100 W. Irving Park Rd. Schaumburg, IL , 60193			
T 1-800-247-3368 or 1-847-534-6000 sales@bisco.com - www.bisco.com 1.4. Emergency telephone number			
Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted	: CHEMTREC - 24-Hour Hazmat Emergency Communications Center Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted		
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or mixture			
GHS US classification			
Skin corrosion/irritation Category 2H315Causes skin irritationSerious eye damage/eye irritation Category 2H319Causes serious eye irritationSkin sensitization, Category 1H317May cause an allergic skin reactionFull text of H statements : see section 16H317H317			
2.2. GHS Label elements, including precautionary statements			
GHS US labeling			
Hazard pictograms (GHS US) :			
Signal word (GHS US) : Warning Hazard statements (GHS US) : H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation			
Precautionary statements (GHS US) : P261 - Avoid breathing dust, fume, vapors. P264 - Wash hands thoroughly after handling P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection P302+P352 - If on skin: Wash with plenty of water and soap P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 - Specific treatment (see First aid measures on this label) P322+P313 - If skin irritation occurs: Get medical advice/attention. P302+P313 - If skin irritation occurs: Get medical advice/attention.	1/12		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ytterbium Fluoride	CAS-No.: 13760-80-0	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319
BisGMA	CAS-No.: 1565-94-2	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
Urethane Dimethacrylate	CAS-No.: Proprietary	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
Ethoxylated Bis A Dimethacrylate	CAS-No.: 41637-38-1	5 - 10	Aquatic Chronic 4, H413
Triethylene Glycol Dimethacrylate	CAS-No.: 109-16-0	1 - 5	Skin Sens. 1B, H317
Tetrahydrofurfuryl Methacrylate	CAS-No.: 2455-24-5	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Trimethylolpropane Trimethacrylate	CAS-No.: 3290-92-4	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after skin contact Symptoms/effects after eye contact	Irritation. May cause an allergic skin reaction.Eye irritation.	
4.3. Immediate medical attention and special treatment, if necessary		

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media				
Suitable extinguishing media	: Water spray. Dry powder. Foam.			
5.2. Specific hazards arising from the chemical				
Hazardous decomposition products in case of fire	: Toxic fumes may be released.			
5.3. Special protective equipment and precautions for fire-fighters				
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.			

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipme	ent and emergency procedures	
6.1.1. For non-emergency personnel		
Emergency procedures :	Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust, fume, vapors.	
6.1.2. For emergency responders		
Protective equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containment an	d cleaning up	
Methods for cleaning up : Other information :	Mechanically recover the product. Dispose of materials or solid residues at an authorized site.	

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust, fume, vapors.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection 8.1. Control parameters No additional information available 8.2. Appropriate engineering controls Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment. 8.3. Individual protection measures/Personal protective equipment Hand protection: Protective gloves Eye protection: Safety glasses Skin and body protection: Wear suitable protective clothing Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density		Solid Viscous Paste. Tooth Acrylic No data available No data available No data available Not applicable No data available No data available Non flammable. No data available No data available No data available No data available
Solubility	:	No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 No data available Not applicable No data available Not applicable Not applicable No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (dermal)	Not classified Not classified Not classified			
Ethoxylated Bis A Dimethacrylate (41637-38-1)				
LD50 oral rat	> 2000 mg/kg Source: ECHA			
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read- across, Dermal, 15 day(s))			
Triethylene Glycol Dimethacrylate (109-16-0)				
LD50 oral rat	10837 mg/kg Source: NLM,THOMSON			
LD50 dermal	> 2000 mg/kg body weight (US EPA, 14 day(s), Mouse, Male, Experimental value, Skin, 14 day(s))			
ATE US (oral)	10837 mg/kg body weight			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrahydrofurfuryl Methacrylate (2455-24-5)				
LD50 oral rat	≈ 4000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)			
Trimethylolpropane Trimethacrylate (3290-92-4)				
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))			
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))			
LD50 dermal rabbit	17120 mg/kg (Rabbit)			
ATE US (dermal)	17120 mg/kg body weight			
Skin corrosion/irritation :	Causes skin irritation.			
Ethoxylated Bis A Dimethacrylate (41637-38-1)			
рН	4.7 (< 0.01 %, 20 °C, OECD 105: Water Solubility)			
Triethylene Glycol Dimethacrylate (109-16-0)				
рН	6.8 - 7.2			
Tetrahydrofurfuryl Methacrylate (2455-24-5)				
рН	No data available in the literature			
Trimethylolpropane Trimethacrylate (3290-92-	-4)			
рН	5.7 (20.1 mg/l, 20 °C, OECD 105: Water Solubility)			
Serious eye damage/irritation :	Causes serious eye irritation.			
Ethoxylated Bis A Dimethacrylate (41637-38-1)				
рН	4.7 (< 0.01 %, 20 °C, OECD 105: Water Solubility)			
Triethylene Glycol Dimethacrylate (109-16-0)				
рН	6.8 - 7.2			
Tetrahydrofurfuryl Methacrylate (2455-24-5)				
рН	No data available in the literature			
Trimethylolpropane Trimethacrylate (3290-92-4)				
рН	5.7 (20.1 mg/l, 20 °C, OECD 105: Water Solubility)			
Respiratory or skin sensitization :	May cause an allergic skin reaction.			
5 ,	Not classified			
• •	Not classified			
Ytterbium Fluoride (13760-80-0)				
IARC group	4 - Probably not carcinogenic to humans			
	Not classified			
	Not classified			
BisGMA (1565-94-2)				
STOT-single exposure	May cause respiratory irritation.			
Urethane Dimethacrylate (Proprietary)				
STOT-single exposure	May cause respiratory irritation.			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrahydrofurfuryl Methacrylate (2455-24-5)				
STOT-single exposure	May cause respiratory irritation.			
STOT-repeated exposure : Not classified				
Triethylene Glycol Dimethacrylate (109-16-0)				
LOAEC (inhalation,rat,gas,90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:			
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)			
NOAEC (inhalation,rat,gas,90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:			
Trimethylolpropane Trimethacrylate (3290-92-4)				
LOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)			
LOAEL (dermal,rat/rabbit,90 days)	300 mg/kg body weight Animal: rabbit			
NOAEL (oral,rat,90 days)	300 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:			
NOAEL (dermal,rat/rabbit,90 days)	300 mg/kg body weight Animal: rabbit			
•	Not classified Not applicable			
Ethoxylated Bis A Dimethacrylate (41637-38-1)				
Viscosity, kinematic	No data available in the literature			
Tetrahydrofurfuryl Methacrylate (2455-24-5)				
Viscosity, kinematic	2.74 mm ² /s (20 °C, OECD 114: Viscosity of Liquids)			
Trimethylolpropane Trimethacrylate (3290-92	-4)			
Viscosity, kinematic	6.166 mm²/s			
• •	Irritation. May cause an allergic skin reaction. Eye irritation.			

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adve effects in the environment.			
BisGMA (1565-94-2)			
LC50 - Fish [1]	0.537 mg/l Source: ECOSAR		
Ethoxylated Bis A Dimethacrylate (41637-38-1)			
LC50 - Fish [1]	h [1] > 100 mg/l Source: ECAH		
EC50 72h - Algae [1]	lgae [1] > 100 mg/l Source: ECAH		
Triethylene Glycol Dimethacrylate (109-16-0)			
LC50 - Fish [1]	16.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)		
Least and the second	•		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylene Glycol Dimethacrylate	(109-16-0)
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	72.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Tetrahydrofurfuryl Methacrylate (24	155-24-5)
LC50 - Fish [1]	34.7 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	97.3 mg/l (Invertebrata, Fresh water)
LC50 - Fish [2]	60.9 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	97.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Trimethylolpropane Trimethacrylate	e (3290-92-4)
LC50 - Fish [1]	0.731 mg/l Source: Ecological Structure Activity Relationships
EC50 - Crustacea [1]	> 9.22 mg/l Test organisms (species): Daphnia magna
ErC50 algae	3.88 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

BisGMA (1565-94-2)			
Persistence and degradability	Biodegradability in water: no data available.		
Ethoxylated Bis A Dimethacrylate (41637-38-1)			
Persistence and degradability	Not readily biodegradable in water.		
Triethylene Glycol Dimethacrylate (109-16-0)			
Persistence and degradability	Readily biodegradable in water.		
Tetrahydrofurfuryl Methacrylate (2455-24-5)			
Persistence and degradability	Readily biodegradable in water.		
Trimethylolpropane Trimethacrylate (3290-92-4)			
Persistence and degradability	sistence and degradability Not readily biodegradable in water. Inherently biodegradable.		
12.3. Bioaccumulative potential			
BisGMA (1565-94-2)			
Partition coefficient n-octanol/water (Log Pow)	4.94 (Estimated value)		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BisGMA (1565-94-2)			
Bioaccumulative potential	No bioaccumulation data available.		
Ethoxylated Bis A Dimethacrylate (41637-38-1)			
Partition coefficient n-octanol/water (Log Pow)	5.62 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)		
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).		
Triethylene Glycol Dimethacrylate (109-16-0)			
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Tetrahydrofurfuryl Methacrylate (2455-24-5)			
Partition coefficient n-octanol/water (Log Pow)	1.76 (Experimental value, EU Method A.8: Partition Coefficient, 22.6 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Trimethylolpropane Trimethacrylate (3290-92-4)			
BCF - Fish [1]	270.1 l/kg (BCFBAF v3.01, Pisces, Fresh water, Calculated value)		
Partition coefficient n-octanol/water (Log Pow)	4.193 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)		
Bioaccumulative potential	Potential for bioaccumulation (4 \leq Log Kow \leq 5).		

12.4. Mobility in soil

Ethoxylated Bis A Dimethacrylate (41637-38-1)		
Surface tension	No data available in the literature	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.56 - 3.88 (log Koc, Calculated value)	
Ecology - soil	Low potential for mobility in soil.	
Triethylene Glycol Dimethacrylate (109-16-0)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.89 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Tetrahydrofurfuryl Methacrylate (2455-24-5)		
Surface tension	No data available in the literature	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.402 - 1.765 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Trimethylolpropane Trimethacrylate (3290-92-4)		
Surface tension	53 mN/m (20 °C, 0.951 g/l, OECD 115: Surface Tension of Aqueous Solutions)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.245 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)	
Ecology - soil	Low potential for mobility in soil.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	;	
13.1. Disposal methods		
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
SECTION 14: Transport information		
In accordance with DOT / TDG / IMDG / IATA		
14.1. UN number		
Not regulated for transport		
14.2. UN proper shipping name		
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Not applicable Not applicable Not applicable Not applicable 	
14.3. Transport hazard class(es)		
DOT Transport hazard class(es) (DOT)	: Not applicable	
TDG Transport hazard class(es) (TDG)	: Not applicable	
IMDG Transport hazard class(es) (IMDG)	: Not applicable	
IATA Transport hazard class(es) (IATA)	: Not applicable	
14.4. Packing group		
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	 Not applicable Not applicable Not applicable Not applicable 	
14.5. Environmental hazards		
Other information	: No supplementary information available.	
14.6. Special precautions for user		
DOT No data available		
TDG No data available		
IMDG No data available		
6/26/2023 (Revision date)	EN (English US)	10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ΙΑΤΑ

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Urethane Dimethacrylate	CAS-No. Proprietary	5 - 10%
Ytterbium Fluoride	CAS-No. 13760-80-0	10 - 30%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

BisGMA (1565-94-2)

Listed on the Canadian DSL (Domestic Substances List)

Ethoxylated Bis A Dimethacrylate (41637-38-1)

Listed on the Canadian DSL (Domestic Substances List)

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on the Canadian DSL (Domestic Substances List)

Tetrahydrofurfuryl Methacrylate (2455-24-5)

Listed on the Canadian DSL (Domestic Substances List)

Trimethylolpropane Trimethacrylate (3290-92-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Tetrahydrofurfuryl Methacrylate (2455-24-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 06/26/2023

Full text of H-phrases		
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	
H413	May cause long lasting harmful effects to aquatic life	

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Added	
	Precautionary statements (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
	Signal word (GHS US)	Added	
	Supersedes	Added	
	Issue date	Removed	
2.1	GHS-US classification	Modified	
3	Composition/Information on ingredients	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
6	Emergency procedures	Modified	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Modified	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.