

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 6/12/2023 Supersedes: 08/10/2020 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : TheraBase Catalyst

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For Rx Only

1.3. Supplier

Manufacturer

BISCO, Inc.

1100 W. Irving Park Rd. Schaumburg, IL , 60193

U.S.A.

T 1-800-247-3368 or 1-847-534-6000 sales@bisco.com - www.bisco.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center

Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

H315

Causes skin irritation

Causes serious eye irritation

Causes serious eye irritation

May cause an allergic skin reaction

Specific target organ toxicity - Single exposure, Category 3,

H335

May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H335 - May cause respiratory irritation P261 - Avoid breathing dust fume yapprs

Precautionary statements (GHS US)

: P261 - Avoid breathing dust, fume, vapors.

P264 - Wash hands thoroughly after handling

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of water and soap

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a poison center/a doctor if you feel unwell

P321 - Specific treatment (see First aid measures on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Glass Filler	CAS-No.: N/A	50 - 75	Eye Irrit. 2, H319 STOT SE 3, H335
10-Methacryloyloxydecyl Dihydrogen Phosphate	CAS-No.: 85590-00-7	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Triethylene Glycol Dimethacrylate	CAS-No.: 109-16-0	10 - 30	Skin Sens. 1B, H317
2-Hydroxyethyl Methacrylate	CAS-No.: 868-77-9	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Tert-butyl Perbenzoate	CAS-No.: 614-45-9	1 - 5	Org. Perox. C, H242 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Triethylamine	CAS-No.: 121-44-8	<1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314
2,6-Di-Tert-Butyl-4-Methylphenol	CAS-No.: 128-37-0	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : May cause eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust, fume, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

6/12/2023 (Revision date) EN (English US) 3/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid breathing dust, fume, vapors. Avoid contact

with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Viscous Resin Paste.

6/12/2023 (Revision date) EN (English US) 4/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color : White Opaque Odor : Acrylic

Odor threshold No data available рΗ No data available No data available Melting point Freezing point Not applicable Boiling point No data available Flash point Not applicable Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) Non flammable. Vapor pressure No data available Relative vapor density at 20°C : No data available Relative density : Not applicable Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable Decomposition temperature : No data available

Decomposition temperature : No data available Viscosity, kinematic : Not applicable Viscosity, dynamic : No data available Explosion limits : Not applicable Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 dermal rat > 20 Exp	12 mg/kg 000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female,	
LD50 dermal rat > 20 Exp	000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female,	
Ехр		
ATE 110 (***- **)	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Skin, 14 day(s))	
ATE US (gases) 450	4500 ppmV/4h	
ATE US (vapors)	mg/l/4h	
ATE US (dust, mist) 1.5	mg/l/4h	
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
	000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental ue, Oral, 14 day(s))	
LD50 dermal rat > 20	000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit > 20	000 mg/kg Source: ECHA	
LC50 Inhalation - Rat (Dust/Mist) > 2	mg/l Source: OSHRI GLP toxicity test	
2-Hydroxyethyl Methacrylate (868-77-9)		
LD50 oral rat 556	64 mg/kg body weight (Rat, Experimental value, Oral)	
LD50 dermal rabbit > 50	000 mg/kg (24 h, Rabbit, Male, Experimental value, Dermal)	
ATE US (oral) 556	64 mg/kg body weight	
Triethylamine (121-44-8)		
LD50 oral rat 730) mg/kg Source: ECHA	
LD50 dermal rabbit 580) mg/kg Source: ECHA	
	ng/l (EPA OTS 798.1150: Acute inhalation toxicity, 4 h, Rat, Male / female, Experimental ue, Converted value, Inhalation (vapours), 14 day(s))	
LC50 Inhalation - Rat [ppm] 349	96 ppm Source: ECHA	
ATE US (oral) 500	mg/kg body weight	
ATE US (dermal) 110	00 mg/kg body weight	
ATE US (gases) 450	00 ppmV/4h	
ATE US (vapors)	mg/l/4h	
ATE US (dust, mist) 1.5	mg/l/4h	
Triethylene Glycol Dimethacrylate (109-16-0)		
LD50 oral rat 108	337 mg/kg Source: NLM,THOMSON	
LD50 dermal > 20 days	000 mg/kg body weight (US EPA, 14 day(s), Mouse, Male, Experimental value, Skin, 14 (s))	
ATE US (oral) 108	337 mg/kg body weight	
Skin corrosion/irritation : Caus	ses skin irritation.	
Tert-butyl Perbenzoate (614-45-9)		
pH No o	data available in the literature	
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
pH No o	data available in the literature	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Hydroxyethyl Methacrylate (868-77-9)	
рН	No data available in the literature
Triethylamine (121-44-8)	
рН	12.5 Source: ECHA
Triethylene Glycol Dimethacrylate (109-1	6-0)
рН	6.8 - 7.2
Serious eye damage/irritation :	Causes serious eye irritation.
Tert-butyl Perbenzoate (614-45-9)	
рН	No data available in the literature
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)	
рН	No data available in the literature
2-Hydroxyethyl Methacrylate (868-77-9)	
рН	No data available in the literature
Triethylamine (121-44-8)	
рН	12.5 Source: ECHA
Triethylene Glycol Dimethacrylate (109-1	6-0)
рН	6.8 - 7.2
Respiratory or skin sensitization :	May cause an allergic skin reaction.
3	Not classified
Carcinogenicity :	Not classified
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)	
NOAEL (chronic,oral,animal/male,2 years)	25 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:
IARC group	3 - Not classifiable
Triethylene Glycol Dimethacrylate (109-1	6-0)
IARC group	4 - Probably not carcinogenic to humans
	Not classified
	May cause respiratory irritation.
10-Methacryloyloxydecyl Dihydrogen Phosph	
STOT-single exposure	May cause respiratory irritation.
Glass Filler (N/A)	
STOT-single exposure	May cause respiratory irritation.
	Not classified
Tert-butyl Perbenzoate (614-45-9)	
NOAEL (oral,rat,90 days)	≈ 30 mg/kg body weight Animal: rat, Guideline: other:
Triethylamine (121-44-8)	
LOAEC (inhalation,rat,dust/mist/fume,90 days)	1.02 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: OECD Guideline 452 (Chronic Toxicity Studies)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylene Glycol Dimethacrylate (109-1	6-0)	
LOAEC (inhalation,rat,gas,90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
NOAEC (inhalation,rat,gas,90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:	
Aspiration hazard :	Not classified	
Viscosity, kinematic :	Not applicable	
Tert-butyl Perbenzoate (614-45-9)		
Viscosity, kinematic	No data available in the literature	
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
Viscosity, kinematic	3.47 mm²/s (0 °C, ASTM D445: Capillary viscometer)	
2-Hydroxyethyl Methacrylate (868-77-9)		
Viscosity, kinematic	6.4 mm²/s (20 °C)	
Triethylamine (121-44-8)		
Viscosity, kinematic	No data available in the literature	
	Irritation. May cause an allergic skin reaction. May cause eye irritation.	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

Ecology - water : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

10-Methacryloyloxydecyl Dihydrogen Phosphate (85590-00-7)		
NOEC chronic fish	48h 10 mg/l	
Tert-butyl Perbenzoate (614-45-9)		
LC50 - Fish [1]	1.6 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
EC50 - Crustacea [1]	11 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	0.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	0.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
ErC50 algae	0.8 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
LC50 - Fish [1]	> 0.57 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
EC50 - Crustacea [1]	0.48 mg/l Test organisms (species): Daphnia magna	
LC50 - Fish [2]	0.199 mg/l (LC50; ECOSAR v1.00; 96 h; Pisces)	
EC50 - Crustacea [2]	0.15 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
EC50 72h - Algae [1]	> 0.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0.023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
2-Hydroxyethyl Methacrylate (868-77-9)		
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value, GLP)	
EC50 - Crustacea [1]	380 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
ErC50 algae	836 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
Triethylamine (121-44-8)		
LC50 - Fish [1]	24 mg/l Source: ECHA	
EC50 72h - Algae [1]	8 mg/l Source: ECHA	
EC50 72h - Algae [2]	6.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	14 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC (chronic)	7.1 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
Triethylene Glycol Dimethacrylate (109-	16-0)	
LC50 - Fish [1]	16.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	72.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)	
LOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

12.2. Persistence and degradability

TheraBase Catalyst		
Persistence and degradability	May cause long-term adverse effects in the environment.	
Tert-butyl Perbenzoate (614-45-9)		
Persistence and degradability	Readily biodegradable in water.	
ThOD	2.14 g O□/g substance	
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.51 g O□/g substance	
Chemical oxygen demand (COD)	2.27 g O□/g substance	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)		
ThOD	2.977 g O□/g substance	
BOD (% of ThOD)	0.17	
2-Hydroxyethyl Methacrylate (868-77-9)		
Persistence and degradability Biodegradability in soil: no data available. Readily biodegradable in water.		
Triethylamine (121-44-8)		
Persistence and degradability	Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.001 g O□/g substance	
Chemical oxygen demand (COD)	1.02 g O□/g substance	
Triethylene Glycol Dimethacrylate (109-16-0)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

TheraBase Catalyst	
Bioaccumulative potential	Not established.
Tert-butyl Perbenzoate (614-45-9)	
Partition coefficient n-octanol/water (Log Pow)	3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)	
Partition coefficient n-octanol/water (Log Pow)	4.17 (Experimental value, 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).
2-Hydroxyethyl Methacrylate (868-77-9)	
Partition coefficient n-octanol/water (Log Pow)	0.42 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.
Triethylamine (121-44-8)	
BCF - Fish [1]	< 0.5 (OECD 305: Bioconcentration: Flow-Through Fish Test, 42 day(s), Cyprinus carpio, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	1.45 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Triethylene Glycol Dimethacrylate (109-1	6-0)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Tert-butyl Perbenzoate (614-45-9)	
Surface tension	No data available in the literature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tert-butyl Perbenzoate (614-45-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, QSAR, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)	
Surface tension	Not applicable (water solubility < 1 mg/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.362 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
2-Hydroxyethyl Methacrylate (868-77-9)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.164 - 0.708 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.
Triethylamine (121-44-8)	
Surface tension	20.05 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.03 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Triethylene Glycol Dimethacrylate (109-	16-0)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.89 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

10-Methacryloyloxydecyl Dihydrogen Phosphate	CAS-No. 85590-00-7	10 - 30%
Glass Filler	CAS-No. N/A	50 - 75%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

and 40 of RV alt 0/2.				
Triethylamine	CAS-No. 121-44-8	< 1%		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylamine (121-44-8)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	5000 lb	

15.2. International regulations

CANADA

10-Methacryloyloxydecyl Dihydrogen Phosphate (85590-00-7)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Tert-butyl Perbenzoate (614-45-9)

Listed on the Canadian DSL (Domestic Substances List)

2,6-Di-Tert-Butyl-4-Methylphenol (128-37-0)

Listed on the Canadian DSL (Domestic Substances List)

2-Hydroxyethyl Methacrylate (868-77-9)

Listed on the Canadian DSL (Domestic Substances List)

Triethylamine (121-44-8)

Listed on the Canadian DSL (Domestic Substances List)

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Tert-butyl Perbenzoate(614-45-9)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
2,6-Di-Tert-Butyl-4-Methylphenol(128-37-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Triethylamine(121-44-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/12/2023 Other information : None.

Full text of H-phrases		
H225	Highly flammable liquid and vapor	
H242	Heating may cause a fire.	
H302	Harmful if swallowed	
H312	Harmful in contact with skin	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H335	May cause respiratory irritation	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	

Indication of changes:					
Section	Changed item	Change	Comments		
	Revision date	Added			
	Supersedes	Added			
	Issue date	Removed			
2	Hazard statements (GHS US)	Modified			
2.1	GHS-US classification	Modified			
3	Composition/Information on ingredients	Modified			

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.