



Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 6/23/2023 Supersedes: 3/20/2018 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Porcelain Etchant (9.5%HF)

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For Rx Only

1.3. Supplier

Manufacturer

BISCO, Inc.
1100 W. Irving Park Rd.
Schaumburg, IL , 60193
U.S.A.
T 1-800-247-3368 or 1-847-534-6000
sales@bisco.com - www.bisco.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (dermal) Category 1	H310	Fatal in contact with skin
Acute toxicity (inhalation:vapor) Category 3	H331	Toxic if inhaled
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H331 - Toxic if inhaled

Precautionary statements (GHS US) :

P260 - Do not breathe fume, vapors.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water and soap
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor
P321 - Specific treatment (see First aid measures on this label)
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Hydrofluoric Acid, 7% ≤ conc ≤ 60%, aqueous solutions	CAS-No.: 7664-39-3	10 - 30	Skin Corr. 1, H314

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Immediately consult a doctor/medical service.
First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Call a physician immediately. Rinse skin with water/shower.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Call a physician immediately. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe fume, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Absorb spillage to prevent material-damage.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Do not breathe fume, vapors.
Handling temperature : 20 - 25 °C
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature : 20 - 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Gel.
Color	: Yellow
Odor	: Odorless
Odor threshold	: No data available
pH	: ≈ 0
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: > 1
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Finely divided metals.

10.5. Incompatible materials

Metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed
Acute toxicity (dermal) : Fatal in contact with skin.
Acute toxicity (inhalation) : Toxic if inhaled.

Porcelain Etchant (9.5%HF)	
LD50 oral rat	> 2000
ATE US (dermal)	5 mg/kg body weight
ATE US (vapors)	3 mg/l/4h

Hydrofluoric Acid, 7%≤conc≤60%, aqueous solutions (7664-39-3)

LD50 dermal rabbit	≤ 50 mg/kg Source: ECHA
--------------------	-------------------------

Skin corrosion/irritation : Causes severe skin burns.
pH: ≈ 0

Hydrofluoric Acid, 7%≤conc≤60%, aqueous solutions (7664-39-3)

pH	< 1
----	-----

Serious eye damage/irritation : Assumed to cause serious eye damage
pH: ≈ 0

Hydrofluoric Acid, 7%≤conc≤60%, aqueous solutions (7664-39-3)

pH	< 1
----	-----

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Hydrofluoric Acid,7%<=conc<=60%,aqueous solutions (7664-39-3)	
LC50 - Fish [1]	51 mg/l Test organisms (species): other:
LC50 - Fish [2]	165 mg/l Test organisms (species): other:
EC50 72h - Algae [1]	43 - 122 mg/l Source: ECHA
NOEC (chronic)	14.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	4 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '21 d'

12.2. Persistence and degradability

Hydrofluoric Acid,7%<=conc<=60%,aqueous solutions (7664-39-3)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Hydrofluoric Acid,7%<=conc<=60%,aqueous solutions (7664-39-3)	
Partition coefficient n-octanol/water (Log Pow)	-0.9 (Calculated)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Hydrofluoric Acid,7%<=conc<=60%,aqueous solutions (7664-39-3)	
Ecology - soil	No (test)data on mobility of the component(s) available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No : UN1790
UN-No. (TDG) : UN1790
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : 1790

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Hydrofluoric acid
Proper Shipping Name (TDG) : HYDROFLUORIC ACID
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Hydrofluoric acid

14.3. Transport hazard class(es)


DOT

Transport hazard class(es) (DOT) : 8 (6.1)
Hazard labels (DOT) : 8, 6.1



TDG

Transport hazard class(es) (TDG) : 8 (6.1)
Hazard labels (TDG) : 8, 6.1




IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : 8 (6.1)
Hazard labels (IATA) : 8, 6.1



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : I
Packing group (IMDG) : Not applicable
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1790
DOT Special Provisions (49 CFR 172.102)	: A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging. A7 - Steel packaging must be corrosion-resistant or have protection against corrosion. B15 - Packaging must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N5 - Glass materials of construction are not authorized for any part of a packaging which is normally in contact with the hazardous material. N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material. T8 - 4 178.274(d)(2) Normal..... Prohibited TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP12 - This material is considered highly corrosive to steel.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 243
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 12 - Keep as cool as reasonably practicable, 40 - Stow "clear of living quarters"

TDG

UN-No. (TDG)	: UN1790
ERAP Index	: 1 000
Explosive Limit and Limited Quantity Index	: 0
Passenger Carrying Ship Index	: Forbidden

IMDG

No data available

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
ERG code (IATA)	: 8P

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Hydrofluoric Acid, 7% ≤ conc ≤ 60%, aqueous solutions	CAS-No. 7664-39-3	10 - 30%
---	-------------------	----------

Hydrofluoric Acid, 7% ≤ conc ≤ 60%, aqueous solutions (7664-39-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	100 lb

15.2. International regulations

CANADA

Hydrofluoric Acid, 7% ≤ conc ≤ 60%, aqueous solutions (7664-39-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Hydrofluoric Acid, 7% ≤ conc ≤ 60%, aqueous solutions (7664-39-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/23/2023

Full text of H-phrases

H310	Fatal in contact with skin
------	----------------------------

Porcelain Etchant (9.5%HF)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H314	Causes severe skin burns and eye damage
H331	Toxic if inhaled

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Added	
	Precautionary statements (GHS US)	Modified	
	Supersedes	Added	
	Issue date	Removed	
	Hazard statements (GHS US)	Modified	
	Signal word (GHS US)	Added	
2.1	GHS-US classification	Modified	
3	Composition/Information on ingredients	Modified	
5.1	Suitable extinguishing media	Modified	
5.2	Hazardous decomposition products in case of fire	Added	
6	Emergency procedures	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
8.2	Respiratory protection	Modified	
8.2	Personal protective equipment	Modified	
8.2	Eye protection	Modified	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.